



General Features and Benefits

- Solid aesthetic appearance
- Frame size: 80mm
- Ability to have doors 2400mm high
- Ability to have stacking doors (see sapphire stacking sliding doors)
- Solid tubular interlock sections
- Adjustable precision ball bearing rollers
- Sill tread to door opening
- Glazed in accordance with Australian Standard AS1288
- Ability to be fitted with optional flydoor or safety door
- Stainless steel fixings
- All mechanical joints fully gasketed
- Lead time typically 7-10 working days
- Backed by our 10 year guarantee
- Robust, long-lasting powder coat finish

Stud Opening	1500	1860	2100	2460
Doors	1450	1810	2050	2410
2125	2095	2095	2095	2095
	SSD2115-2	SSD2118-2	SSD2121-2	SSD2124-2
Stud Opening	2754	3114	3654	
Doors	2704	3064	3604	
2125	2095	2095	2095	
	SSD2127-3	SSD2130-3	SSD2136-3	
	*For end opening 3 panel doors X00 and 00X configuration add 32mm to the total width of door.			
Stud Opening	2932	3648	4128	4848
Doors	2882	3598	4078	4798
2125	2095	2095	2095	2095
	SSD2129-4	SSD2136-4	SSD2141-4	SSD2148-4
Stud Opening	2217	2757	3117	3657
Doors	2167	2707	3067	3607
2125	2095	2095	2095	2095
	SSD2121-3-STK	SSD2127-3-STK	SSD2130-3-STK	SSD2136-3-STK
Stud Opening	4364	5444	6164	
Doors	4314	5394	6114	
2125	2095	2095	2095	
	SSD2142-6-STK	SSD2154-6-STK	SSD2161-6-STK	



Scenic Windows Vic. Pty. Ltd.

43 - 45 Progress Street, Dandenong 3175 Victoria Australia
 Telephone: 03 9701 3088 Facsimile: 03 9701 3096
 Email: sales@scenicwindows.com.au
 Website: www.scenicwindows.com.au

All windows are viewed from outside. All windows shown are 700 pascal rating. For higher rating windows contact your Scenic Windows representative.

