


Counter Balance Double Hung Window Specifications

- Glazing in windows complies with AS 1288. Wind Region A. Exposed Suburban
- Purchaser to specify if window conditions vary from this
- These products are designed to 1000pa wind pressure and 150pa water pressure
- All frames are viewed from the outside

STUD OPENING	630	785	935	1230	1230	1530	1830	2420	2725	
FRAME	610	765	915	1210	1210	1510	1810	2400	2705	
1077	1057									
		CB1006	CB1008	CB1009	CB1012M	CB1012	CB1015	CB1018	CB1024	CB1027
1217	1197									
		CB1206	CB1208	CB1209	CB1212M	CB1212	CB1215	CB1218	CB1224	CB1227
1417	1397									
		CB1406	CB1408	CB1409	CB1412M	CB1412	CB1415	CB1418	CB1424	CB1427
1517	1497									
		CB1506	CB1508	CB1509	CB1512M	CB1512	CB1515	CB1518	CB1524	CB1527
1817	1797									
		CB1806	CB1808	CB1809	CB1812M	CB1812	CB1815	CB1818	CB1824	CB1827
2127	2107									
		CB2106	CB2108	CB2109	CB2112M	CB2112	CB2115	CB2118	CB2124	CB2127
2417	2397									
		CB2406	CB2408	CB2409	CB2412M	CB2412	CB2415	CB2418	CB2424	CB2427

These configurations / sizes are provided as a guide. Homeview can manufacture this product to suit most openings. Timber and aluminium flywire screens are available with this product. Lockable and non-lockable hardware is also available. Options are only available at time of ordering Please note: Some frames may require doors or sashes removed upon delivery and or onsite glazing depending on size



Counter Balance System

The Counter Balance window is effectively a vertical sliding window that offers a combination of the look of weights and cords and a modern Counter Balance system which utilises the weight of one sash to counter the weight of the other.



1 Standard 2 Colonial Bar 3 Colonial Bar 4 Heritage Bar 5 Federation Bar

Our commitment to continual product development necessitates that sizes and specifications may change without notice.